

Bumpered Fog Nozzles



Features

- Straight stream, capable of greater than 100° spray angle
- Twist shut-off and flow-type change

Specification

- Maximum working pressure: **100 PSI**; maximum rated pressure: **175 PSI**

Approvals

- FM Approved for class A and B fires
- UL certified for class A and B fires



BBN75

| Size | Thread | Rated Flow at Rated Pressure (GPM) | Rated Flow at Wide Open: GPM @ 100 PSI | Approvals | | | Brass Part # |
|------|--------|------------------------------------|--|-----------|----|-----|--------------|
| | | | | FM | UL | ULC | |
| 3/4" | GHT | 54 | 54 | ✓ | ✓ | ✓ | BBN75GHT |
| | NPSH | | | ✓ | ✓ | ✓ | BBN75 |
| 1" | NPSH | 60 | 60 | ✓ | ✓ | ✓ | BBN100 |
| | NST | | | ✓ | ✓ | ✓ | BBN100NST |

Global Approved Fog Nozzles



Applications

- Industrial
- Rack and reel assemblies

Feature

- Straight stream, fog, shut-off

Specification

- Maximum working pressure: **150 PSI** (water only)

Approvals

- FM Approved
- UL certified, ULC Listed



| Size | Thread | Brass Part # |
|--------|--------|--------------|
| 1-1/2" | NPSH | GBN150 |
| | NST | GBN150NST |
| 2-1/2" | NST | GBN250NST |