

BR-Series Pneumatic Couplings

Features:

- Interchange data: Rectus 21KA, Tomco Series SC, CEJN Series 223
- Nitrile (Buna-N) seals are standard temperature range **-40°F to 250°F (-40°C to 121°C)**
- pressure rating: **300 PSI**

Female Threaded Plugs

Body Size	Threads	Brass Part #
1/8"	1/8" - 27 NPT	BR1F1-B-E-7 BR1BF1-B-E-7 BR1F2-B-E-7 BR1BF2-B-E-7
	1/8" - 28 BSPP	
	1/4" - 18 NPT	
	1/4" - 19 BSPP	



Male Threaded Plugs

Body Size	Threads	Brass Part #
1/8"	1/8" - 27 NPT	BR1M1-B-E-7 BR1GM1-B-E-7 BR1M2-B-E-7 BR1GM2-B-E-7
	1/8" - 28 BSPP	
	1/4" - 18 NPT	
	1/4" - 19 BSPP	



Female Threaded Couplers

Body Size	Threads	Brass Part #
1/8"	1/8" - 27 NPT	1BRF1-B-7 1BRBF1-B-7 1BRF2-B-7 1BRBF2-B-7
	1/8" - 28 BSPP	
	1/4" - 18 NPT	
	1/4" - 19 BSPP	



Male Threaded Couplers

Body Size	Threads	Brass Part #
1/8"	1/8" - 27 NPT	1BRM1-B-7 1BRGM1-B-7 1BRM2-B-7 1BRGM2-B-7
	1/8" - 28 BSPP	
	1/4" - 18 NPT	
	1/4" - 19 BSPP	



Hose Barb Plugs

Body Size	Hose ID	Brass Part #
1/8"	4mm	BR1S1.25-B-E-7 BR1S1.86-B-E-7 BR1S2.83-B-E-7
	6mm	
	9mm	



Hose Barb Couplers

Body Size	Hose ID	Brass Part #
1/8"	4mm	1BRS1.25-B-7 1BRS1.86-B-7 1BRS2.83-B-7
	6mm	
	9mm	

