

### Wharf Hydrants



**Features:**

- used to provide a fire department outlet connection
- pentagon nut at top of spindle discourages unauthorized use
- hydrostatically tested
- maximum operating pressure: **300 PSI at 70°F (21°C)**

Inlet Female NPT	Outlet Male NST (NH)	Height Open	Height Closed	Cast Brass Part #
3"	2½"	16.38	14.25	<b>WHYD3025F</b>
4"	2½"	16.38	14.25	<b>WHYD4025F</b>
4"	4½"	18.13	15.63	<b>WHYD4045F</b>

### Replacement Parts



hand wheel




pentagon hex nut

Description	Part #
optional hand wheel	<b>46-030-00025</b>
pentagon hex nut	<b>44-251-00006</b>

### Forestry Grade ¼ Turn Ball Type Wye Valves



1" - 1½"



2½"

**Features:**

- cast aluminum swivel inlet, anodized body, hard-coated threads
- built to US Forest Service specifications
- 1" and 1½" for use up to **600 PSI** (water/AFFF only); 2½" for use up to **400 PSI** (water/AFFF only)

Female Thread	(2) Male Threads	Cast Aluminum Part #
1" NPSH	1" NPSH	<b>FWV10S10S</b>
1½" NPSH	1½" NPSH	<b>FWV15S15S</b>
1½" NST (NH)	1½" NST (NH)	<b>FWV15F15F</b>
2½" NST (NH)	1½" NST (NH)	<b>FWV25F15F</b>
2½" NST (NH)	2½" NST (NH)	<b>FWV25F25F</b>