



Dixon® Mill Hose

Ideal for open end discharge or washdown applications.

All Synthetic Single Jacket Mill Hose

Application:

- used in open end water discharge applications only; not intended for fire fighting service



Features:

- outer construction: single jacket, all polyester
- tube construction: black, PVC rubber
- rated pressure: **250 PSI** at ambient temperature 70°F (21°C)
- working pressure: **125 PSI** at ambient temperature 70°F (21°C)
- contact Dixon® for pricing and availability on 75' lengths and other threads and configurations



Uncoupled

Size	Bowl	Length	Part #
1"	1¼"	50'	M10-50UC
1"	1¼"	100'	M10-100UC
1½"	1 ¹¹ / ₁₆ "	25'	M15-25UC
1½"	1 ¹¹ / ₁₆ "	50'	M15-50UC
1½"	1 ¹¹ / ₁₆ "	100'	M15-100UC
2"	2 ³ / ₈ "	25'	M20-25UC
2"	2 ³ / ₈ "	50'	M20-50UC
2"	2 ³ / ₈ "	100'	M20-100UC
2½"	2 ¹¹ / ₁₆ "	25'	M25-25UC
2½"	2 ¹¹ / ₁₆ "	50'	M25-50UC
2½"	2 ¹¹ / ₁₆ "	100'	M25-100UC
3"	3 ³ / ₈ "	25'	M30-25UC
3"	3 ³ / ₈ "	50'	M30-50UC
3"	3 ³ / ₈ "	100'	M30-100UC
4"	4 ³ / ₈ "	25'	M40-25UC
4"	4 ³ / ₈ "	50'	M40-50UC
4"	4 ³ / ₈ "	100'	M40-100UC
6"	6 ³ / ₈ "	25'	M60-25UC
6"	6 ³ / ₈ "	50'	M60-50UC

Coupled with female and male expansion ring couplings



Size	Length	Aluminum NPSH Part #	Aluminum NST (NH) Part #	Aluminum MNPT x MNPT Part #
1½"	50'	M15-50RAS	M15-50RAF	M15-50RAT
1½"	100'	M15100RAS	M15100RAF	M15100RAT
2"	50'	M20-50RAS	---	M20-50RAT
2"	100'	M20100RAS	---	M20100RAT
2½"	25'	M25-25RAS	M25-25RAF	---
2½"	50'	M25-50RAS	M25-50RAF	M25-50RAT
2½"	100'	M25100RAS	M25100RAF	M25100RAT

Refer to dixonvalve.com for Synthetic Single Jacket Mill Hose coupled with:

- female and male King™ short shank couplings, crimp sleeve
- female and male (C & E) global aluminum cam and groove

All Synthetic Double Jacket Mill Hose

Application:

- ideal for open end discharge applications, not intended for fire fighting service



Features:

- outer construction: double jacket, all polyester
- tube construction: black, PVC rubber
- rated pressure: **250 PSI** at 70°F
- working pressure: **200 PSI** at 70°F



Uncoupled

Size	Bowl	Length	Part #
1½"	1 ¹³ / ₁₆ "	50'	DM15-50UC
	1 ¹³ / ₁₆ "	100'	DM15-100UC
2"	2 ⁵ / ₁₆ "	50'	DM20-50UC
	2 ⁵ / ₁₆ "	100'	DM20-100UC
2½"	2 ⁷ / ₈ "	50'	DM25-50UC
	2 ⁷ / ₈ "	100'	DM25-100UC



Coupled with female and male rocker lug, aluminum expansion ring couplings

Size	Bowl	Length	NST (NH) thread Part #	NPSH thread Part #	NPT thread Part #
1½"	1 ¹³ / ₁₆ "	50'	DM15-50RAF	DM15-50RAS	DM15-50RAT
	1 ¹³ / ₁₆ "	100'	DM15100RAF	DM15100RAS	DM15100RAT
2"	2 ⁵ / ₁₆ "	50'	---	DM20-50RAS	DM20-50RAT
	2 ⁵ / ₁₆ "	100'	---	DM20100RAS	DM20100RAT
2½"	2 ⁷ / ₈ "	50'	DM25-50RAF	DM25-50RAS	DM25-50RAT
	2 ⁷ / ₈ "	100'	DM25100RAF	DM25100RAS	---



Coupled with female and male (C & E) global aluminum cam and groove, crimp sleeve

Size	Bowl	Length	Part #
1½"	1 ¹³ / ₁₆ "	50'	DM15-50GAX
		100'	DM15100GAX
2"	2 ⁵ / ₁₆ "	50'	DM20-50GAX
		100'	DM20100GAX

Consult Dixon® for pricing and availability for any of the following options:

- 75' lengths
- other threads and configurations

Dixon Fire

800 High Street • Chestertown, MD 21620
 ph: 877.963.4966 • fx: 410-778-4702 • 800-283-4966
dixonvalve.com

